



DIMENSIONES Y ESPECIFICACIONES DE RPC



Dimensiones
L x A = 60 x 40 cm (23.6 x 15.8 plg)

Palé Entrante
Altura del Palé = 6 plg

Palé Saliente
Altura del Palé = 6 plg

	Modelo	Altura External		Peso Prom. Vacío (lbs)	RPCs Plegado/ Palé (ctd)	Altura Total del Palé (plg)	RPCs Llenos Máx. /Palé (ctd)	Altura Máx. del Palé (plg)
		(cm)	(plg)					
SERIE IFCO	6408	10.3	4.1	3.1	165	53.6	110	85
	6411	13.3	5.2	3.3	165	53.6	85	90
	6413	14.8	5.8	3.5	165	53.6	75	89
	6416	18.4	7.2	3.9	165	53.6	60	89
	6419	21.0	8.3	4.2	165	53.6	55	94
	6423	24.8	9.8	4.9	105	53.8	45	91
	6425	27.3	10.8	5.3	105	53.8	40	90
SERIE LIFT LOCK	6408N/LL	10.3	4.1	2.8	195	53.8	110	87
	6411N/LL	13.4	5.3	3.2	195	53.8	85	89
	6413N/LL	14.9	5.9	3.4	195	53.8	75	88
	6416N/LL	18.5	7.3	3.8	195	53.8	60	89
	6419N/LL	21.1	8.3	4.2	195	53.8	55	92
	6423N/LL	24.5	9.7	4.6	125	53.4	45	90
	6425N/LL	27.0	10.6	5.0	125	53.4	40	88
	6428N/LL	29.0	11.4	5.5	105	53.4	40	95
	6429N/LL	29.1	11.5	5.3	125	53.4	40	95
	6421BC	22.4	8.8	4.1	270	81.9	45	85

Altura Paletizada (en pulgadas; palé = 6 plg)

	Ctd/Palé	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110
		SERIE IFCO	6408	28	32	36	40	43	47	51	55	58	62	22	70	73	77	81
	6411	36	40	45	50	55	60	65	70	75	80	85	90					
	6413	39	45	50	56	61	67	72	78	83	89							
	6416	48	55	61	68	75	82	89										
	6419	54	62	70	78	86	94											
	6423	63	72	82	91													
	6425	69	79	90														
SERIE LIFT LOCK	6408N/LL	28	32	35	39	43	47	50	54	58	61	65	59	72	76	80	83	87
	6411N/LL	35	40	45	50	55	60	65	70	75	80	84	89					
	6413N/LL	39	44	50	55	61	66	72	77	83	88							
	6416N/LL	47	54	61	68	75	82	89										
	6419N/LL	54	62	70	77	85	92											
	6423N/LL	62	71	80	90													
	6425N/LL	68	78	88														
	6428N/LL	73	84	95														
	6429N/LL	73	84	95														
	6421BC	85																

IFCO SYSTEMS US

A Brambles Company

877-430-IFCO | info.na@ifco.com

www.IFCO-US.com | www.worldwide-responsibility.com

